Photocontrol - NIGHTFOX Specifier Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only

Item LED4536SCMX

PRODUCT DESCRIPTION

Photocontrol specifically designed for 20-year service to match the life expectancy of long-life LED and new induction fixtures.

FEATURES

- Non-drift silicon light sensor with IR filter.
- DC relay with zero-crossing circuitry for extended life.
- All components meet 20-year life expectancy.
- Conformal coated PCB.
- Exceeds 15,000 ON/OFF switching cycles.
- Ideal for single or multi-fixture HID and LED installations (up to 2,220 W @ 277 VAC).
- 510 J MOV surge protection.
- High precision, microprocessor-controlled zero-cross switching, individually calibrated to extend the life of 20 A relay independent of load being switched.

APPLICATIONS

- Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	LED4536SCMX
Description	NIGHTFOX Specifier Grade Locking Type Electronic Photocontrol, 120-277 V, Mexico Sales Only
UPC Code	078275143647
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	12-Year limited

Control Specifications	
Sensor Time Delay	Instant ON; 2 sec to 5 sec OFF
Photocell Type	Silicon Diode
Photo Control Switch Type	Relay
Fail Mode	ON
Activation On	1.5 fc
Activation Off	2.25 fc
Photocontrol Type	Electronic
Application Compatibilities	LED; Incandescent; HID
Photocontrol Style	Locking type
Photocontrol Sensor Location	Side

Dimensions	
Product Height (in)	2.75
Product Height (mm)	69.9
Product Diameter (in)	3.375
Product Diameter (mm)	85.8

Material Specifications	
Color	White with Blue Band
Housing Material	Polypropylene

Load Ratings	
Magnetic Ballast (NO) Range(s)	1800 VA
Electronic Ballast (NO) Range(s)	8 A, 120-277 VAC
Tungsten Incandescent (NO) Range(s)	1000 W

Electrical Specifications	
Input Voltage Range(s)	120-277 VAC, 50/60 Hz (Nominal Voltage)
Operating Voltage Range(s)	102-305 VAC
Surge Protection Technology	510 J MOV
Equipment operating voltage	102 - 305 V

Packaging	
Shipping Weight (lbs)	0.3
Unit Carton Dimensions (H x W x D) in	3.25 x 3.19 x 3.19 in

Operating Specifications	
Expected Lifetime (Years)	20
Expected Lifetime (Operations)	15000

Environmental Specifications	
Temperature (operation)	-40 °F to 158 °F / (-40 °C to 70 °C)
Usage Environments	Outdoor

Standards and Certifications	
UL Certification	cULus
Other Certifications and Compatibilities	NOM; ANSI C136.10
California Proposition 65	None
RoHS Certification	N/A

© 10/21/2026

ACCESSORIES

K121
Locking Type Receptacle, 3-Pin, C136.10 Compliant, 9" lead

K121-30
Locking Type Receptacle, 3-Pin, C136.10 Compliant, 30" lead

K122
Locking Type Receptacle, 3-Pin, C136.10 Compliant, with Pole Mounting Bracket

K171H
Locking Type Receptacle, 7-Pin, C136.41 Compliant, 12" lead

KPT0170-010
PowerTap Receptacle, 7-Pin, C136.41 Compliant, Always-On, 10' cable

KPT1170-010
PowerTap Receptacle, 7-Pin, C136.41 Compliant, Dusk-to-Dawn, 10' cable

SK4500K
Shorting Plug for Locking Type Receptacles

KPT0170-015
PowerTap Receptacle, 7-Pin, C136.41 Compliant, Always-On, 15' cable

SK4500KMX
Shorting Plug for Locking Type Receptacles