In-Wall Timer - Spring Wound Countdown Timer, Mechanism Only, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, Without Hold

Item FF5M10



PRODUCT DESCRIPTION

The FF Series Commercial Countdown Timers are designed to replace any standard wall switch and do not require electricity to operate. These energy-efficient switches automatically limit the ON times for fans, lighting, motors, heaters, and other energy consuming loads. A commercial "brushed metal" look plate (plastic construction) meets NEC requirements. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- Mechanism only.
- 5-Minute timer.
- SPST (Single-Pole Single-Throw).
- Breaks circuit at end of timing cycle.
- No electricity required to operate.
- Replaces any standard or decorator single-gang wall switch.
- Automatically limits ON time for energy consuming loads.
- Quick and easy installation.
- Time-saving up front terminal connection with teeter-type terminals.
- Brushed metal look switch plate meets NEC requirements (plate is included).

TECHNICAL DATA

General	
Model Number	FF5M10
Description	Spring Wound Countdown Timer, Mechanism Only, 125-277 VAC, 50/60 Hz, SPST, 5 Minute Max, Without Hold
UPC Code	078275003057
Brand	Intermatic
Country of Origin (Intermatic)	TUNISIA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Material Specifications	
Color	Black
Finish	Brushed Metal

Load Ratings	
Resistive Heater	20 A, 2500 W, 125 VAC; 10 A, 2500 W, 250 VAC; 10 A, 2770 W, 277 VAC
Tungsten Incandescent (NO) Range(s)	7 A, 125 VAC, 875 W

Electrical Specifications	
Input Voltage Range(s)	125-277 VAC, 50/60 Hz
Switch Type	SPST

Environmental Specifications	
Temperature (operation)	40 - 120 °F / 4 - 49 °C

Packaging	
Shipping Weight (lbs)	0.249

Technical specifications and other information are subject to change without notice. Images can vary from original.

Unit Carton Dimensions (H x W x D) in	4.63 x 2.13 x 2.88 in

Standards and Certifications	
UL Certification	RU
CSA Certification	cCSAus
California Proposition 65	DEHP
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.