Weatherproof Cover - Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 2.25" Clear

Item WP1220C



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly, and inserts to meet the needs of a variety of applications.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick neoprene gasket with slits for mounting screws.
- Six inserts provided with all models that allow each model to meet multiple installations (up to 70 configurations).
- Max cord size: (2) #14 AWG or (1) #12 AWG, WP1250 (2) #14 AWG or (1) #10 AWG.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1220C
Description	Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 2.25" Clear
UPC Code	078275072695
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	6
Insert Types Included	WP217
Hinge Direction	Vertical
Cold Impact Testing Temperature (°C)	-51
Cold Impact Testing Temperature (°F)	-60
Cover Gasket	3mm
Enclosure Type	Outdoor type 3R plastic
Is Extra-Duty Rated	No
Number of Gangs	Double
Electrical Box Shape	Square

Dimensions	
Product Dimensions (H x W x D) in	5.5 x 5 x 2.25 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Double

Material Specifications	
Color	Clear

Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.444
Unit Carton Dimensions (H x W x L) in	3.001 x 5.501 x 5.501 in

Standards and Certifications	
UL Certification	cULus
Compliance	2020 NEC Article 314.15; CEC Article 26-702
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP217
Double-Gang Inserts (6)