Weatherproof Cover - Plastic In-Use Weatherproof Cover, Single-Gang, Vrt, 2.25" Clear

Item WP1000C



PRODUCT DESCRIPTION

The WP1000C In-Use Weatherproof Cover provides dependable protection for single-gang receptacles in outdoor, damp, and wet-location applications. Constructed from heavy-duty, UV-stabilized polycarbonate, this clear cover features a pre-adhered 3 mm neoprene gasket and is tested for cold impact down to -60°F (-51°C) for reliable performance in demanding environments. Three included inserts accommodate up to eight installation configurations, providing flexibility for a variety of receptacle applications. UL Certified for Type 3R outdoor enclosures and featuring a compact 2.25-inch depth with a vertical hinge, the WP1000C delivers durable, versatile protection for outdoor electrical connections.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws.
- Three inserts provided with all models that allow each model to meet multiple installations (up to 8 configurations).
- Max cord size: (2) #14 AWG or (1) #12 AWG.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1000C
Description	Plastic In-Use Weatherproof Cover, Single-Gang, Vrt, 2.25" Clear
UPC Code	078275022515
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle

Dimensions	
Product Dimensions (H x W x D) in	5.5 x 3.8 x 2.25 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single

Material Specifications	
Color	Clear
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.444
Unit Carton Dimensions (H x W x L) in	8.13 x 5.5 x 3.56 in

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP17
Single-Gang Inserts (3)