Weatherproof Cover - Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 4.75" Clear

Item WP1150C



PRODUCT DESCRIPTION

The WP1150C In-Use Weatherproof Cover provides dependable protection for single-gang receptacles in outdoor, damp, and wet-location applications. Constructed from heavy-duty, UV-stabilized polycarbonate, this clear cover features a pre-adhered 3 mm neoprene gasket and is tested for cold impact down to -60°F (-51°C) for reliable performance in demanding environments. Three included inserts accommodate up to 16 installation configurations, while the versatile design supports both vertical and horizontal mounting. UL Certified for Type 3R outdoor enclosures and featuring a generous 4.75-inch depth, the WP1150C offers a durable and flexible solution for protecting outdoor electrical connections.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws.
- Three inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations).
- Max cord size: (2) #14 AWG or (1) #12 AWG.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1150C
Description	Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 4.75" Clear
UPC Code	078275072831
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle

Dimensions	
Lockable Hasp Maximum Diameter (in)	.25
Lockable Hasp Maximum Diameter (mm)	6
Product Dimensions (H x W x D) in	5.375 x 3.5 x 4.75 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single

Material Specifications

Color	Clear
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.444
Unit Carton Dimensions (H x W x L) in	5.001 x 4.501 x 6.251 in

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP17
Single-Gang Inserts (3)