Weatherproof Cover - Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 4.75" Clear

Item WP1250C



PRODUCT DESCRIPTION

The WP1250C In-Use Weatherproof Cover provides reliable protection for double-gang receptacles in outdoor, damp, and wet-location applications. Constructed from heavy-duty, UV-stabilized polycarbonate, this clear cover features a 3 mm neoprene gasket and is tested for cold impact down to -60°F (-51°C) for dependable performance in demanding environments. Six included inserts accommodate up to 70 installation configurations, providing added flexibility for a variety of receptacle setups. UL Certified for Type 3R outdoor enclosures, the WP1250C combines durable construction, versatile installation options, and a generous 4.75-inch depth for dependable outdoor receptacle protection.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick neoprene gasket with slits for mounting screws.
- Six inserts provided with all models that allow each model to meet multiple installations (up to 70 configurations).
- Max cord size: (2) #14 AWG or (1) #12 AWG, WP1250 (2) #14 AWG or (1) #10 AWG.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP1250C
Description	Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, 4.75" Clear
UPC Code	078275072718
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	6
Insert Types Included	WP217
Hinge Direction	Vertical
Is Extra-Duty Rated	No
Number of Gangs	Double
Electrical Box Shape	Square

Dimensions	
Product Dimensions (H x W x D) in	6 x 5 x 4.75 in
Accepted Cord Size Max	2x14 AWG; 1x10 AWG
Box Type	Double

Material Specifications	
Color	Clear
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.701
Unit Carton Dimensions (H x W x L) in	5.251 x 5.501 x 6.501 in

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	N/A

ACCESSORIES



WP217
Double-Gang Inserts (6)