
Weatherproof Cover - Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, White

Item WP7200W



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- 100% Paintable surface.
- Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications.
- CEC Article 26-702 Compliant.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts.
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws.
- Lockable hasp: All models accept up to 0.19" dia shank.
- Impact rated: 12 lbf. impact test to ensure cover remains intact.
- Reinforced hinge pin designed to exceed 40 lbf. hinge hang/stress test.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP7200W
Description	Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Double-Gang, Vrt, White
UPC Code	078275149946
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	4
Hinge Direction	Vertical
Is Extra-Duty Rated	Yes
Number of Gangs	Double
Electrical Box Shape	Square

Dimensions	
Lockable Hasp Maximum Diameter (in)	0.19
Lockable Hasp Maximum Diameter (mm)	4.8
Product Dimensions (H x W x D) in	5.5 x 5.609 x 1.5 in
Expandable Depth Mm	54
Expandable Depth In	2 1/8
Accepted Cord Size Max	1x16 AWG
Box Type	Double

Technical specifications and other information are subject to change without notice. Images can vary from original.

Material Specifications	
Color	Clear; White
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.5
Unit Carton Dimensions (H x W x L) in	5.45 x 5.6 x 1.45 in

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	Y

Technical specifications and other information are subject to change without notice. Images can vary from original.