Weatherproof Cover - Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Clear

Item WP3100CMX



NOM

PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include adhered gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- Complies with 2020 NEC Article 314.15 for damp and wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick, pre-adhered neoprene gasket with slits for mounting screws.
- Lockable hasp: All models accept up to 1/4" (6 mm) dia shank, except WP3100C & WP3103C accept up to 1/8" (3 mm) dia shank.
- Three inserts provided with all models that allow each model to meet multiple installations (up to 16 configurations).
- Max cord size: (2) #14 AWG or (1) #12 AWG.
- Mounts vertically or horizontally.
- Warranty: 1-year limited.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP3100CMX
Description	Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, 2.75" Clear
UPC Code	078275106093
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	3
Insert Types Included	WP17
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle

Dimensions	
Lockable Hasp Maximum Diameter (in)	1/8
Lockable Hasp Maximum Diameter (mm)	3
Product Dimensions (H x W x D) in	5.771 x 4 x 2.755 in
Accepted Cord Size Max	2x14 AWG; 1x12 AWG
Box Type	Single

Material Specifications	
Color	Clear

Technical specifications and other information are subject to change without notice. Images can vary from original.

Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.402
Unit Carton Dimensions (H x W x L) in	2.639 x 4.069 x 5.759 in

Standards and Certifications	
Other Certifications and Compatibilities	NOM
California Proposition 65	None
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.