Weatherproof Cover - Low-Profile Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, Bronze

Item WP6000BR



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- 100% Paintable surface.
- Complies with 2020 NEC Article 314.15 for wet locations.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base and inserts.
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws.
- Lockable hasp: All models accept up to 0.19" dia shank.
- Impact rated: 12 lbf. impact test to ensure cover remains intact.
- Warranty: 1-year limited.
- NEW Faster Installation, Pre-Set for GFCI, No insert required.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP6000BR
Description	Low-Profile Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, Bronze
UPC Code	078275149922
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	2
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	No
Number of Gangs	Single
Electrical Box Shape	Rectangle

Dimensions	
Lockable Hasp Maximum Diameter (in)	0.19
Lockable Hasp Maximum Diameter (mm)	4.8
Product Dimensions (H x W x D) in	5.5 x 3.75 x 1.5 in
Expandable Depth Mm	54
Expandable Depth In	2 1/8
Accepted Cord Size Max	1x16 AWG
Box Type	Single

Material Specifications	
Color	Clear; Bronze

Technical specifications and other information are subject to change without notice. Images can vary from original.

Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x L) in	1.5 x 3.7 x 5.5 in
Product Weight (lbs)	0.35
Product Weight (kg)	0.159

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	Y