Weatherproof Cover - Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, Clear, 3/0 Adapter Plate

Item WP7003G



PRODUCT DESCRIPTION

Plastic In-Use Weatherproof Covers are easy to install and include a gasket, mounting screws, base, cover assembly and inserts to meet the needs of a variety of applications.

FEATURES

- Includes 3/0 adapter plate for 3" (76 mm) round box.
- 100% Paintable surface.
- Complies with 2020 NEC Article 406.9 (B)(1) for wet locations and extra-duty applications.
- Exceeds CEC Section 26-702.
- UL Certified for Type 3R outdoor enclosures.
- Meets requirements for cold impact testing: -60° F (-51° C).
- Heavy-duty UV stabilized polycarbonate cover, mounting base, and inserts.
- 1/8" (3 mm) thick, neoprene gasket with slits for mounting screws.
- Lockable hasp: All models accept up to 0.19" dia shank.
- Impact rated: 12 lbf. impact test to ensure cover remains intact.

APPLICATIONS

- Receptacle Protection

TECHNICAL DATA

General	
Model Number	WP7003G
Description	Low-Profile Extra-Duty Plastic In-Use Weatherproof Cover, Single-Gang, Vrt/Hrz, Clear, 3/0 Adapter Plate
UPC Code	078275150539
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Mechanical Specifications	
Number of Included Inserts	2
Hinge Direction	Vertical/Horizontal
Is Extra-Duty Rated	Yes
Number of Gangs	Single
Electrical Box Shape	Rectangle; Round

Dimensions	
Lockable Hasp Maximum Diameter (in)	0.019
Lockable Hasp Maximum Diameter (mm)	4.8
Product Dimensions (H x W x D) in	5.5 x 3.75 x 1.5 in
Expandable Depth Mm	54
Expandable Depth In	2.125
Accepted Cord Size Max	1x16 AWG
Box Type	Single

Technical specifications and other information are subject to change without notice. Images can vary from original.

Material Specifications	
Color	Clear; Gray
Weatherproof Cover Material	UV Stabilized Plastic

Packaging	
Shipping Weight (lbs)	0.5
Unit Carton Dimensions (H x W x L) in	1.675 x 4 x 5.5 in

Standards and Certifications	
UL Certification	cULus
California Proposition 65	None
RoHS Certification	Y

Technical specifications and other information are subject to change without notice. Images can vary from original.