In-Wall Timer - 7-Day Standard Programmable Timer, 120 VAC, 12A, Light Almond

Item EJ600A



PRODUCT DESCRIPTION

12 A rated timer that provides full 7-day programming capabilities with dusk-to-dawn functionality, ideal for use with medium to low power loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly. Wall plate not included.

FEATURES

- 7-day programmable schedules with 14 ON/OFF events.
- Astronomic clock feature determines dawn and dusk times.
- Automatic Daylight Saving Time (DST) adjustment.
- Random mode varies ON/OFF schedule to provide a "lived-in" appearance.
- Single or 3-way switch compatible installation.
- Incandescent/fluorescent compatible.
- Built-in rechargeable, non-serviceable battery backup.
- Requires neutral connection.
- Decorator switch plate not included.

APPLICATIONS

- Indoor Lighting Control
- Air Movement & Ventilation
- Outdoor Lighting Control

TECHNICAL DATA

General	
Model Number	EJ600A
Description	7-Day Standard Programmable Timer, 120 VAC, 12A, Light Almond
UPC Code	078275127883
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited
TARIC HS Code	9107.00.00

Control Specifications	
Minimum ON/OFF Times	1 min
Time Presets	Flexible
Operation Mode	24 hour
Operation Features	Astronomic; Daylight Saving Time
Mechanism Type	Digital/Electronic
Backup Type	Battery
Backup Protection Time	100 Hours
Battery Service Type	Non-Replaceable
Application Compatibilities	Incandescent; Fluorescent
Chemical Composition of the Battery Cell	Li-ion
On Events	7
Off Events	7
Total Events	14

Mechanical Specifications

Wall Plate Configurations	Single-Gang
Dimensions	
Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.438 in
Material Specifications	
Color	Light Almond
Includes Wall Plate	No
Finish	Gloss
Load Ratings	
Resistive Heater	12 A, 1440 W
Incandescent Single Gang Load Ratings Ranges	15 A, 120 VAC
Incandescent Multi Gang Load Ratings Ranges	12 A, 120 VAC
Tungsten Incandescent (NO) Range(s)	1440 W Multigang; 1800 W Singlegang
Electrical Specifications	
Input Voltage Range(s)	120 VAC, 60 Hz
Wiring Configurations	Single; 3-Way
Neutral Connection Required	Yes
Environmental Specifications	
Temperature (operation)	32 - 104 °F / 0 - 40 °C
Packaging	
Shipping Weight (lbs)	0.35
Unit Carton Dimensions (H x W x D) in	6.13 x 2.13 x 3 in
Standards and Certifications	
CSA Certification	cCSAus
Other Certifications and Compatibilities	Green Energy
California Proposition 65	DEHP
RoHS Certification	N/A

Technical specifications and other information are subject to change without notice. Images can vary from original.